REZID 10-17-06 8WY OK

Lee Surveying and Mapping Co., Inc.

Land Surveys • Topography • Subdivisions • Construction Layout

117 N. Madriver St. Bellefontaine OH 43311



Phone: (937) 593-7335 Fax: (937) 593-7444

1975-2005 - 30 Years of excellence

YEASEL, TRUSTEE 5.631 ACRES

Lying in Section 16, Town 7, Range 8, Bloomfield Township, Logan County, Ohio.

Being out of the Phyllis B. Yeasel, Trustee of the Phyllis B. Yeasel Trust, dated February 17, 1994, 75.23 acre tract as deeded and described in Official Record 433, Page 045, Tract I, First Parcel of the Logan County Records of Deeds and being more particularly described as follows:

Commencing on a railroad spike found on the north line of Section 16, on the intersection of center-lines of County Highway 21 and Ohio Route 274.

THENCE, with the north line of Section 16 and the center-line of Ohio Route 274 (60 feet wide), S 89°-53'-00"E, a distance of 536.53 feet to a MAG nail set at the TRUE POINT OF BEGINNING, passing a point at the northwest corner of the northeast quarter of Section 16 at 27.40 feet.

THENCE, with the north line of Section 16 and the center-line of Ohio Route 274, S 89°-53'-00"E, a distance of 58.21 feet to a MAG nail set.

THENCE, with the lines of the Shelby Wilson, Trustee of the GST Perpetuities Trust of the C. Dean Yeasel Trust Agreement, dated February 17, 1994, 1.95 acre tract (O.R. 386, Pg. 147), the following three courses:

S 0° - 07° - 00° W, a distance of 370.00 feet to a 5/8 inch iron rod set, passing a 5/8 inch iron rod set at 30.00 feet.

S 89°-53'-00"E, a distance of 230.00 feet to a point on a building.

STATE OF

LEE 6359

S/ONAL SU

ORIGINAL STAMP IN GREEN

N 0°-07'-00"E, a distance of 370.00 feet to a MAG nail set on the north line of Section 16 and the center-line of Ohio Route 274, passing a MAG nail set at 1.00 feet and a 5/8 inch iron rod set at 333.01 feet.

THENCE, with the north line of Section 16 and the center-line of Ohio Route 274 (variable widths), S 89°-53'-00"E, a distance of 248.32 feet to a MAG nail set.

THENCE, S 0°-11'-14"E, a distance of 615.82 feet to a 5/8 inch iron rod set.

THENCE, N 89°-53'-00"W, a distance of 536.53 feet to a 5/8 inch iron rod set.

THENCE, N 0°-11'-14"W, a distance of 615.82 feet to the point of beginning, passing a 5/8 inch iron rod set at 585.82 feet.

Containing 5.631 acres, of which 0.277 acre is within the highway right-of-way.

The basis for bearings is the north line of Section 16, being N 89°-53'-00"W, and all other bearings are from angles and distances measured in a field survey by Lee Surveying and Mapping Co., Inc. on October 13, 2006.

Description prepared by:

Jeffrey 1. Lee

Professional Surveyor 6359

October 13, 2006

4316096



PECID 10-17-04 SWM OK

TATE OF

LEE

ONAL

ORIGINAL STAMP IN GREEN

Lee Surveying and Mapping Co., Inc.

Land Surveys • Topography • Subdivisions • Construction Layout

117 N. Madriver St. Bellefontaine OH 43311



Phone: (937) 593-7335 Fax: (937) 593-7444

1975-2005 - 30 Years of excellence

YEASEL, TRUSTEE 7.585 ACRES

Lying in Section 16, Town 7, Range 8, Bloomfield Township, Logan County, Ohio.

Being out of the Phyllis B. Yeasel, Trustee of the Phyllis B. Yeasel Trust, dated February 17, 1994, 75.23 acre tract and 20.00 acre tract as deeded and described in Official Record 433, Page 045, Tract I, First Parcel and Third Parcel of the Logan County Records of Deeds and being more particularly described as follows:

Beginning on a railroad spike found on the north line of Section 16, on the intersection of center-lines of County Highway 21 and Ohio Route 274.

THENCE, with the north line of Section 16 and the center-line of Ohio Route 274 (60 feet wide), S 89°-53'-00"E, a distance of 536.53 feet to a MAG nail set, passing a point at the northwest corner of the northeast quarter of Section 16 at 27.40 feet.

THENCE, S 0° -11'-14"E, a distance of 615.82 feet to a 5/8 inch iron rod set, passing a 5/8 inch iron rod set at 30.00 feet.

THENCE, N 89°-53'-00"W, a distance of 536.53 feet to a MAG nail set on the center-line of County Highway 21, passing a 5/8 inch iron rod set at 506.53 feet.

THENCE, with the center-line of County Highway 21 (60 feet wide), N 0°-11'-14"W, a distance of 615.82 feet to the point of beginning.

Containing 7.585 acres, of which 1.177 acres are within the highway rights-of-way.

The basis for bearings is the north line of Section 16, being N 89°-53'-00"W, and all other bearings are from angles and distances measured in a field survey by Lee Surveying and Mapping Co., Inc. on October 13, 2006.

Description prepared by:

Jeffrey I. Lee

Professional Surveyor 6359

October 13, 2006

4316096



RECID 10-17-04 Suy OL LEGEND: SCAL RAILROAD SPIKE FOUND 1.954 ACRES RAILROAD SPIKE SET OF WHICH 0.173 ACRE IS WITHIN lS THE HIGHWAY RIGHTS-OF-WAY MAG NAIL SET SHELBY WILSON, TRUSTEE OF THE GST PERPETUITIES TRUST OF THE C. DEAN YEASEL TRUST AGREEMENT, DATED FEBRUARY 17, 1994 5/8 INCH IRON ROD SET POINT ON BUILDING 1-1/4 INCH X 1-1/2 INCH DETAIL 1.95 ACRES IRON BAR FOUND OFFICIAL RECORD 386. PAGE 147 NOT TO SCALE RETRACEMENT SURVEY OF THE ,27.40 58.21 -SECTION 9-(BASIS FOR BEARINGS) S 89°53'00" E S 89°53'00" E N 89°53'00" W 274 SHELBY WILSON, TRUSTEE OF THE 536.53 230.00 248.32 18 SECTION 16 729.08 GST PERPETUITIES TRUST OF THE 36 (VARIABLE WIDTHS) 54 C. DEAN YEASEL TRUST AGREEMENT, UNABLE TO SET RIGHT-OF-WAY POINT HIGHWAY DATED FEBRUARY 17, 1994 DUE TO DITCH LOCATION 1.95 ACRE TRACT , 40,00 7.585 ACRES OF THE DATED 00 11 14 OFFICIAL RECORD 386, PAGE 147 615.82 0 Z OF WHICH 1.177 ACRES ARE WITHIN AND SURVEY OF TWO TRACTS OUT OF THE 230.00 THE HIGHWAY RIGHTS-OF-WAY 2 DETAIL N 89°53'00"\W PHYLLIS B. YEASEL, TRUST
PHYLLIS B. YEASEL TRUST
FEBRUARY 17, 199
20.00 ACRES PHYLLIS B. YEASEL, TRUSTEE OF THE 00,11 (7.198 ACRES) 5.631 ACRES HI GHWAY PHYLLIS B. YEASEL, TRUSTEE OF THE PHYLLIS B. YEASEL TRUST, PHYLLIS B. YEASEL TRUST, DATED OF WHICH 0.277 ACRE IS WITHIN (0.387 ACRE) FEBRUARY 17, 1994 DATED FEBRUARY 17, 1994 THE HIGHWAY RIGHT-OF-WAY 75.23 ACRES 75.23 ACRE TRACT AND 20.00 ACRE TRACT 536.53 O.R. 433, PG. 045 536.53 TRACT I, FIRST PARCEL N 89°53'00" W N 89°53'00" W OFFICIAL RECORD 433, PAGE 045 -30.00 TRACT I, FIRST & THIRD PARCEL SECTION 16, TOWN 7, RANGE 8 BLOOMFIELD TOWNSHIP LOGAN COUNTY, OHIO TOWNSHIP ROAD 80 JEFFREY L. LEE PROFESSIONAL SURVEYOR 6359 LEE OCTOBER 13, 2006 6359 2 WORKING DAYS COPYRIGHT 2006 BY: LEE SURVEYING & MAPPING CO., INC. 117 North Madriver Street BELLEFONTAINE, OHIO 43311 ONAL SUR BEFORE YOU DIG PARALLE SULLES CALL TOLL FREE 800-362-2764 ORIGINAL STAMP IN GREEN (937) 593-7335 OHIO UTILITIES PROTECTION SERVICE. **KSR** D1006 4316096 L-4316-3 INDEXED ON MAP