ROYER SURVEY October, 1973

TRACT 2

The following described real estate situated in Virginia Military Survey No.3442, Jefferson Township, Logan County, Ohio and being more particularly described as follows:

Beginning at an iron bar in the centerline of S.R.47 at the northeast corner of George H. Royer's 60.00 acre tract; thence with said centerline N.51°02'E. 150.0 feet to an iron bar; thence S.29°15.5'E. 216.75 feet to an iron bar in the north line of Ruth M. Bailey's 10.5 acre tract; thence with said Bailey's north line S.50°59.7'W. 258.0 feet to an iron bar in the east line of George H. Royer's 60.00 acre tract; thence with said Royer's east line N.4°54.4'W. 258.1 feet to the place of beginning.

Containing 1.00 acre more or less.

The above described 1.00 acre being on the west side of George H. Royer's 2.00 acre tract.

I hereby certify that the above is a true and accurate description of a survey made by me.

Leslie H. Geeslin Reg.Surveyor 5248



S.R. 47 (60°) 182,09" SEURISE H. POYER STUN 60.00Ac 1.00 Ac. 1.00 40 TRACT / TRACT 2 5 50° 597'W. 258.0' \$ 5.50° 57 25.35' RUTH AT BAILEY 10.50 AC ROYER SURVEY 0 = R.R. OPIKE OCTOBER, 1973 V.M. S. 3442 C = 7/8 /20N BAR 0 = 3/4" /120N BPR JEFFERSON TOWNSHIP SEALE 1" = 50" LOGAN COUNTY, OHIO INDEXED ON MAR

LEGLE H. GEESLIN

Lee Surveying and Mapping Co., Inc.

Land Surveys . Topography . Subdivisions . Construction Layout

117 N. Madriver St. Bellefontaine OH 43311



Phone: (937) 593-7335 Fax: (937) 593-7444 surveys@lsminc.us

MARKER 1.082 ACRES

Lying in Virginia Military Survey 3442, City of Bellefontaine, Jefferson Township, Logan County, Ohio.

Being out of the Harold D. Marker and Barbara F. Marker, Trustees 60 acre tract as deeded and described in Official Record 769, Page 146 of the Logan County Records of Deeds and being more particularly described as follows:

Commencing at a railroad spike found at the intersection of center-lines of Township Road 230 and Ohio Route 47 (60 feet wide).

THENCE, with the center-line of Ohio Route 47 the following two courses:

S 50°-00'-36"W, a distance of 1508.00 feet to a railroad spike found at Station 872+30.69 (Logan County Engineer's Plan L-44 sheet 2 of 6).

S 47°-50'00"W, a distance of 781.60 feet to a MAG nail set at the TRUE POINT OF BEGINNING.

THENCE, S 20°-07'-52"E, a distance of 253.86 feet to a 5/8 inch iron rod set, passing a 5/8 inch iron rod set at 32.36 feet.

THENCE, S 66°-37'-57"W, a distance of 213.08 feet to a 5/8 inch iron rod set.

THENCE, N 23°-22'-03"W, a distance of 185.44 feet to a MAG nail set, passing a 5/8 inch iron rod set at 155.41 feet.

THENCE, with the center-line of Ohio Route 47, N 69°-14'-57"E, a distance of 24.38 feet to a railroad spike found at Station 862+36.85 (Logan County Engineer's Plan L-44 sheet 2 of 6).

THENCE, with the center-line of Ohio Route 47, N 47°-50'-00"E, a distance of 214.50 feet to the point of beginning.

Containing 1.082 acres of which 0.164 acre is within the highway right-of-way.

Property is subject to any and all previous easements and rights-of-way of record.

gs is from an apping Co., i The basis for bearings is center-line of Ohio Route 47, being N 47°-50'-00"E, and all other bearings are from angles and distances measured in a field survey by Lee Surveying and Mapping Co., Inc. on August 16, 2011

Description prepared by:

William K. Bruce

Professional Surveyor 7437


August 16, 2011

L-51930811



ONAL

ORIGINAL STAMP IN GREEN



MDEKED ON MAP 5275 2P