

Farm Surveys . Lot Surveys . Topography . Subdivisions . Construction Layout

855 EAST SANDUSKY AVENUE BELLEFONTAINE, OHIO 43311 (513) 593-5780

CLAYTON M. LEE, P.S. JEFFREY I. LEE, P.S.

BRUCK LILE

TRACT 1, V.M.S. 12099

Lying in V.M.S. 12099, Monroe Township, Logan County, Ohio.

Being out of that 7.71 acre tract deeded and described in Volume 384, Page 553 of the Logan County Records of Deeds and more particularly described as follows:

Beginning at an iron rod set on the south line of V.M.S. 12099, marking the southwest corner of said 7.71 acres and also being the southwest corner of this survey.

THENCE, with the west line of said 7.71 acres, N 12°-38'-20" W, a distance of 346.20 feet to an iron rod set on the northwest corner of said 7.71 acres, passing a railroad spike found on the center-line of Township Road 165 at 15.00 feet.

THENCE, with the north line of said 7.71 acres, N $79^{\circ}-14^{\circ}-10^{\circ}$ E, a disatnce of 195.34 feet to an iron rod.

THENCE, S 12°-12'-45" E, a distance of 343.65 feet to an iron rod set on the south line of V.M.S. 12099, passing an iron spike set on the center-line of Township Road 165 at 328.65 feet.

THENCE, with the south line of V.M.S. 12099, 3 78°-30' W, a distance of 192.72 feet to the point of beginning. Containing 1.536 acres.

Last previous deed reference: Volume 384, Page 553.

Surveyed by:

Clayton M. Lee

Reg. Surveyor No. 6181

9/11/79

INDEXED ON MAP & WASHINGTON TO THE WASHINGTON TO



Farm Surveys . Lot Surveys . Topography . Subdivisions . Construction Layout

855 EAST SANDUSKY AVENUE BELLEFONTAINE, OHIO 43311 (513) 593-5780

CLAYTON M. LEE, P.S. JEFFREY I. LEE, P.S.

BRUCE LILE

TRACT 2, V.M.S. 12099

Lying in V.M.S. 12099, Monroe Township, Logan County, Ohio.

Being out of that 7.71 acre tract deeded and described in Volume 384, Page 553 of the Logan County Records of Deeds and more particularly described as follows:

Beginning at an iron rod set on the south line of V.M.S. 12099, marking the southwest corner of said 7.71 acres and also being the southwest corner of this survey.

THENCE, With the south line of said V.M.S. 12099, N 78°-30° E, a distance of 192.72 feet to an iron rod set for the southwest corner of this survey, and being the True Point of Beginning.

THENCE, N 12°-12'-45" W, a distance of 343.65 feet to an iron rod on the north line of said 7.71 acres, passing an iron spike set on the center-line of Township Road 165 at 15.00 feet.

THENCE, with said north line, N $79^{\circ}-14^{\circ}-10$ E, a distance of 195.34 feet to an iron rod.

THENCE, S 11°-47°-00" E, a distance of 341.10 feet to an iron rod set on the south line of V.M.S. 12099, passing an iron spike set on the center-line of Township Road 165 at 326.10 feet.

THENCE, with the south line of V.M.S. 12099, S 78°-30' W, a distance of 192.72 feet to the point of beginning. Containing 1.525 acres.

Last previous deed reference: Volume 384, Page 553.

Surveyed by:

Clayton W. Lee

Reg. Surveyor No. 6181

9-11-79

100E/ED ON MAP 4340 1D-2



Farm Surveys . Lot Surveys . Topography . Subdivisions . Construction Layout

855 EAST SANDUSKY AVENUE BELLEFONTAINE, OHIO 43311 (513) 593-5780

CLAYTON M. LEE, P.S. JEFFREY I. LEE, P.S.

BRUCE LILE TRACT 3, V.M.S. 12099

Lying in V.M.S. 12099, Monroe Township, Logan County, Ohio.

Being out of that 7.71 acre tract deeded and described in Volume 384. Page 553 of the Logan County Records of Deeds and more particularly described as follows:

Beginning at an iron rod set on the south line of V.M.S. 12099, marking the southwest corner of said 7.71 acres and also being the southwest corner of this survey.

THENCE, with the south line of said V.M.S. 12099, N 78°-30' E, a distance of 385.44 feet to an iron rod set for the southwest corner of this survey, and being the True Point of Beginning

THENCE, N 11°-47'-00" W, a distance of 341.10 feet to an iron rod set on the north line of said 7.71 acres, passing an iron spike set on the center-line of Township Road 165 at 15.00 feet.

THENCE, with said north line, N 79°-14'-10" E, a distance of 195.34 feet to an iron rod.

THENCE, S 11°-20'-40" E, a distance of 338.59 feet to an iron rod set on the south line of V.M.S. 12099, passing an iron spike set on the center-line of Township Road 165 at 323.59 feet.

THENCE, with the south line of V.M.S. 12099, S 78°-30° W, a distance of 192.72 feet to the point of beginning. Containing 1.514 acres.

Last previous deed reference: Volume 384, Page 553.


SURVE TO THE THE PROPERTY OF

Surveyed by:

Clayton M. Lee

Reg. Surveyor No. 6181

9-11-79





Farm Surveys . Lot Surveys . Topography . Subdivisions . Construction Layout

855 EAST SANDUSKY AVENUE BELLEFONTAINE, OHIO 43311 (513) 593-5780

CLAYTON M. LEE, P.S. JEFFREY I. LEE, P.S.

BRUCE LILE SURVEY

TRACT 4

Lying in V.M.S. 12099, Monroe Township, Logan County, Ohio and being out of that 7.71 acre tract deeded and described in Volume 384, Page 553 of the Logan County Records of Deeds and more particularly described as follows:

Beginning at an iron rod set on the south line of V.M.S. 12099 marking the southeast corner of said 7.71 acres.

THENCE, with said south line, S 78°-30' W, a distance of 192.72 feet to an iron rod, THE TRUE POINT OF BEGINNING.

THENCE, N 10°-54' W, a distance of 336.10 feet to an iron rod on the north line of said 7.71 acres, passing an iron rod set on the center-line of Township Road 165 at 15.00 feet.

THENCE, with the north line of the 7.71 acres, S 79°-14'-10" W, a distance of 195.34 feet to an iron rod.

THENCE, S 11°-20'-40" E, a distance of 338.59 feet to the south line of V.M.S. 12099, passing an iron spike set on the center-line of Township Road 165 at 323.59 feet.

THENCE, with said V.M.S. line, N 78°-30° E, a distance of 192.72 feet to the point of beginning. Containing 1.503 acres.

Last previous deed description: Volume 384, Page 553.

Surveyed by:

Clayton W. Lee Reg. Surveyor No. 6181

9-11-79

INDEXED ON MERF





Farm Surveys . Lot Surveys . Topography . Subdivisions . Construction Layout

855 EAST SANDUSKY AVENUE BELLEFONTAINE, OHIO 43311

(513) 593-5780

CLAYTON M. LEE, P.S. JLEFREY I. LEE, P.S.

BRUCE LILE SURVEY

TRACT 5

Lying in V.M.S. 12099, Monroe Twonship, Logan County, Ohio and being off the east side of that 7.71 acres deeded and described in Volume 384, Page 553 of the Logan County Records of Deeds and more particularly described as follows:

Beginning at an iron rod set on the south line of V.M.S. 12099 marking the southeast corner of said 7.71 acres.

THENCE, with said south line, S 78°-30' W, a distance of 192.72 feet, passing the center-line extended of the north-south leg of Township Road 165.

THENCE, N 10°-54' W, a distance of 336.10 feet to an iron rod set on the north line of said 7.71 acres, passing an iron rod set on the center-line of the east-west leg of Township Road 165 at 15.00 feet.

THENCE, with the said north line, N 79°-14'-10" E, a distance of 195.34 feet to a corner stone found at the northeast corner.

THENCE, with the east line of the 7.71 acres, S 10°-26'-55" E, a distance of 333.63 feet to the point of beginning. Containing 1.492 acres.

Last preceding deed reference: Volume 384, Page 553.


Surveyed by:

Clayton M. Lee

Reg. Surveyor No. 6181

9-11-79

6340 D-5



Received 10/6/93

SURVEY FOR DON BRADLEY 4.000 ACRES SEPTEMBER 2, 1993

The following described tract of land is situated in the State of Ohio, County of Logan, Township of Monroe, V.M.S. 12099, V.M.S. 9878, 10109, 10718, 10719, being part of Donald O. Lockwood's original 62.57 acre tract described in deed volume 387, page 848, and being more particularly described as follows:

Beginning for reference at a railroad spike set at the intersection of the centerline of Township Road #165(60 feet wide) with the north line of V.M.S. 9878, 10109, 10718, 10719, the south line of V.M.S. 12099, the north line of Charles R. McClain's 13.57 acre tract described in deed volume 195, page 23, and in the south line of Paul W. and Christine A. Crissinger's 1.492 acre tract described in deed volume 388, page 964 (reference made to Logan County Engineer Survey Field Book 689, page 57 and 58 for positioning the centerline of Township Road #165);

thence North 85°01'04" East (bearing based on an assumed meridian with all others based on angles turned) 12.68 feet, following the north line of V.M.S. 9878, 10109, 10718, 10719, the south line of V.M.S. 12099, the north line of said 13.57 acre tract, and the south line of said 1.492 acre tract, to a 5/8" iron pin set with cap marked "CLAPSADDLE RS 6140" at a northwest corner of said 62.57 acre tract, and marking the place of beginning;

thence North 85°01'04" East 129.71 feet, continuing along the north line of V.M.S. 9878, 10109, 10718, 10719, the south line of V.M.S. 12099, a north line of said 62.57 acre tract, and the south line of said 1.492 acre tract, passing at 24.00 feet a 5/8" iron pin set with cap marked "CLAPSADDLE RS 6140," to a 1/2" iron pin found;

thence North 3°48'58" West 333.89 feet, following the east line of said 1.492 acre tract and a west line of said 62.57 acre tract, to a stone found in the south line of James Edwin and Ladonna Fern Gantz's 265.47 acre tract described in deed volume 280, page 345;

thence North 85°30'56" East 303.28 feet, following the north line of said 62.57 acre tract and the south line of said 265.47 acre tract, to a 5/8" iron pin set with cap marked "CLAPSADDLE RS 6140;"

thence South 14°46'23" West 740.92 feet, entering said 62.57 acre tract and passing at 709.47 feet a 5/8" iron pin set with cap marked "CLAPSADDLE RS 6140," to a railroad spike set in the centerline of Township Road #165 and the south line of said 62.57 acre tract;



thence South 87°18'27" West 185.55 feet, following the centerline of Township Road #165 and the south line of said 62.57 acre tract, passing at 140.44 feet a railroad spike set at an angle point in the centerline of Township Road #165 and at 170.59 feet a 3/4" iron pin found, to a 3/4" iron pin found in the east line of said 13.57 acre tract;

thence North 5°36'42" West 358.74 feet, following the west line of said 62.57 acre tract and the east line of said 13.57 acre tract, crossing the centerline of Township Road #165 at 279.39 feet, to the place of beginning, containing 4.000 acres, more or less, with 1.889 acre being in V.M.S. 12099, and 2.111 acres being in V.M.S. 9878, 10109, 10718, 10719, and with 0.452 acre being within the road right of way of Township Road #165. Subject to all valid easements and restriction of record.

The above description was prepared from an actual field survey made under the supervision of Paul R. Clapsaddle, Registered Surveyor #6140 during the month of September, 1993.

ATTEST:


Paul R. Clapsaddle, Registered Surveyor #6140

CLAPSAPORE & CLAPS

19019 West Darby Road Marysville, Ohio 43040

(513) 747-2599






SURVEY FOR DON BRADLEY

STATE OF OHIO, COUNTY OF LOGAN, TOWNSHIP OF MONROE, V.M.S. 12099

V.M.S. 9878, 10109, 10718, 10719, AND BEING PART OF DONALD O. LOCKWOOD'S

ORIGINAL 62.57 ACRE TRACT DESCRIBED IN DEED VOLUME 387, PAGE 848.

I HEREBY CERTIFY THAT THIS PLAT WAS PREPARED FROM AN ACTUAL FIELD SURVEY MADE UNDER MY SUPERVISION AND THAT MONUMENTS WERE PLACED AS INDICATED.





Paul R. Clapsaddle and Associates

REGISTERED ENGINEERS AND SURVEYORS

19019 WEST DARBY ROAD, MARYSVILLE OHIO 43040 (513) 747-2599 (800) 745-2599

Paul R. Clapsaddle, P.E., P.S.

FILE NAME: BRADL993 DATE: SEPTEMBER 2, 1993 SCALE: 1" = 100' F.B. 11, PG. 1

- I" IRON PIPE FOUND.
- O RAILROAD SPIKE SET.
- 3/4" IRON PIN FOUND.
- 1/2" IRON PIN FOUND.
- 5/8" IRON PIN FOUND.
- A STONE FOUND.
- 5/8" IRON PIN SET WITH CAP MARKED "CLAPSADDLE RS 6140"

REFERENCE MATERIAL: LOG. CO. ENG. F.B. 689, PG. 57, 58 LOG. CO. SURVEY RECORD 6340


REFERENCE DEEDS SHOWN HEREON.

BEARINGS INDICATED HEREON ARE BASED ON AN ASSUMED MERIDIAN WITH ALL OTHERS BASED ON ANGLES TURNED.

INDEXED ON MAP

6340 2P

					ROAD NO 165
EASEMENT FOR HIGHWAY PURPOSES KNOW ALL MEN BY THESE PRESENTS: That We, The Undersigned, the Grantors, for and in consideration of the sum of One Dollar (\$1.00) and for other good and valuable considerations paid by the County of Logan, the Grantee, the receipt whereof is hereby acknowledged, do hereby grant harden soll soles.	STATE OF OHIO SS: LOGAN COUNTY	OFFICE OF THE LOGAN COUNTY ENGINEER This plat has been approved as to ownership this day of	OFFICE OF THE LOGAN COUNTY COMMISSIONERS This plat has been approved and accepted by us this	day of	MONROE TOWNSHIP LOGAN COUNTY, OHIO 2
That, We, The Undersigned, the Grantors, for and in consideration of the sum of One Dollar (\$1.00) and for other good and valuable considerations paid by the County of Logan, the Grantee, the receipt whereof is hereby acknowledged, do hereby grant, bargain, sell, convey and release to the said Grantee, its successors and assigns forever, a perpetual easement and right-of-way for public highway and road purposes, clear of all obstructions which interfere with the improvement and/or maintenance of the highway, in, upon, and over the lands shown on this map. TO HAVE AND TO HOLD said easement and right-of-way unto the Grantee, its successors	Before mea in and for said County and State, personally appeared the above named	Tax Map Draftsman This plat has been approved and accepted by me thisday of	Board of County Commi	issioners.	BALD KNOB ROAD MOOTS MILL ROAD PIPER MILL ROAD
and accides forever		County Engineer		NE.	THE THE TOTAL
and assigns, all right and expectancy of Dower in the above described premises. IN WITNESS WHEREOF WE, the undersigned Grantors, have hereunto set our hands,	who acknowledged thathe did sign the foregoing instrument and that the same isfree act and deed. IN TESTIMONY WHEREOF I have hereunto set my hand and official seal at				
Lord, one thousand nine hundred and Signed and sealed in the presence of:	thisday of,A.D. I9 My Commission Expires	1836 Section 0.00 to 1.08			SE
2. Office feit Earl Juster		Comm. Journal 5, Page 105 60' Right of Way	5	N. S	
3. Ed Danis Gal feet trules 4. La Porna Hands Gyl is freit				Scale: "=100"	
5. Paul W. Crisenger Ell Let Trusto					
7. Jan J. Wallon End Life Trusta					
9. Janet McClain Cal Late tousto				JAMES EDWIN AND ZAL MAP No. 137-00-003	PONNA FERN GANTZ H/W.
10. A Howland & appenter the				VOL. 280 PAGE 345	
12. Glendora Keller Egy Freil				175.61 ACRE	0
13. Polist Ffloral Cost Sal Suido					2091/0109
15. Joan Maples Effe Freit Carl List Truste				253	46.
Villan 1 Line God His Feil				7.50	1. V. Vo. 10,
				8.77 ACRES	1. N. 10 11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
			ROBERT F. AND EDITH R. HURST		FI F STA. 32+66.39 A=0009.6'Rr.
	BONNIE M. GRUBBS MAP No. 123-00-73	The contract of the contract o	MAR No. 137-00-002 Vol. 316 PAGE 797 (9-29-1967)	H/W.	30'30' WOOD
$\frac{ e _{\mathcal{I}}}{ \mathcal{O} }$	VOL. 333 PAGE 647 (1-29-1971) 135.04 ACRES		28.83 ACRES		Appropriate Corner Post
10.15		100			Proof of the state
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\			AREA IN ROADY 0.80 ACRES	D. D	1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
		3/4 \$ IRON BAR P.I. STA. 16+69.24 $\Delta = 39^{\circ}-03.1' \ R\tau.$	AREA IN ROADWAY 0.03 ACRES	C.STA. 27+	- TOX 05: 25
Z IRON BAR	AREA IN ROADWAY	D = 23°-28.3' T = 87.18' R = 245.83' E = 15.00'	PROPERTY CORNER TR. R. SPIKE Fo. STA. 17+57.11 (NO ANGLE)	BRIDGE 165-0500	
STA. 0+00 (T.R. No. 165) = STA. 168+57.26 (C.H. No. 5)		Z = 166.38'		45°-44.3'E. # 25+00 8. L.	3/4" & IRON BAR P.I. STA. 28+26.34
mo om on one of the original	P 5+00	o win	BRIDGE 165-0.32	3/4" \$ IRO P.I. STA. 26+ D= 24°-04.3	97.00 D=30°-11.8' 'ZT: T=65.90'
	5.38°-03.4'E.	10+00	2 11 15	D = 18°-36.7 T = 65.90' R = 309.21' AREA IN ROADWAY 1.10 ACRES E = 6.95'	E = 11.00' L = 125.51'
		R B	6 th C 2	AREA IN ROADWAY 1.10 ACRES £ = 6.95' L = 129.34'	
	AREA IN ROADWAY 1.20 ACRES.	1"\$ IRON BAR P.I. STA. 13+38.18			
		$\Delta = 46^{\circ} - 44.0' Z_{T}.$ $D = 37^{\circ} - 13.1'$ $T = 67.70'$ $R = 156.70'$		ROBERT F. AND EDITH R. HURST H/W. MAP NO. 137-00-002 VOL. 316 PAGE 797 (9-29-1967)	DON E. AND M. JOAN MAPLES MAP NO. 137-00-030 VOL. 380 PAGE 792 (12-16-1978)
		E = 14.00' L = 125.57'		67.40 ACRES	82.59 ACRES
	EARL I. AND EFFIE L. LEIG MAP No. 137-00-01 VOL. 314 PAGE 451 (5-5-1				
	123.00 ACRE	5		Constitution of the second	SURVEYED BY DANIEL E. GILBERT, P.S.
				INDEXED ON MAP G340 3P-1	DRAWN BY DANIEL E. GILBERT, P.S. JANUARY 1985
					Original @ Engineer's Office)



RECID 12-17-09 SWM ONV

Lee Surveying and Mapping Co., Inc.

Land Surveys . Topography . Subdivisions . Construction Layout

117 N. Madriver St. Bellefontaine OH 43311



Phone: (937) 593-7335 Fax: (937) 593-7444 surveys@lsminc.us

WALBORN 7.114 ACRES

Lying in Virginia Military Survey 12099, Monroe Township, Logan County, Ohio.

Being all of the Julie A. Walborn 9.5 acre tract as deeded and described in Official Record 859, Page 894 of the Logan County Records of Deeds and being more particularly described as follows:

Beginning on a MAG nail set on the south line of Virginia Military Survey 12099 on the center-line of Township Road 166.

THENCE, with the center-line of Township Road 166 (66 feet wide), N 07°-02'-29"E, a distance of 399.48 feet to a MAG nail set, passing a 5/8 inch iron rod found on the intersection of the center-line of Township Road 165 at 14.22 feet.

THENCE, with the south line of the James E. Gantz and LaDonna F. Gantz, Trustees, 182.937 acre tract (O.R. 820, Pg. 627), N 76°-11'-06"E, a distance of 780.82 feet to a 5/8 inch iron rod set, passing a 5/8 inch iron rod set at 35.31 feet.

THENCE, with the west line of the Philip Moots two acre tract (Vol. 43, Pg. 172), S 16°-15'-14"E, a distance of 349.92 feet to a 5/8 inch iron rod set on the south line of Virginia Military Survey 12099, passing a 5/8 inch iron rod set at 319.92 feet.

THENCE, with the south line of Virginia Military Survey 12099, S 74°-44'-15"W, a distance of 938.24 feet to the point of beginning.

Containing 7.114 acres, of which 1.216 acres are within the highway rights-of-way.

The basis for bearings is the center-line of Township Road 165 between P.I. Station 44+15.04 and Station 49+83.75, being N 74°-48'-24"E, and all other bearings are from angles and distances measured in a field survey by Lee Surveying and Mapping Co., Inc. on December 8, 2009.

BRUCE X BRUCE X BRUCE OF COMMINION OF COMMIN

Description prepared by:

William K. Bu

William K. Bruce Professional Surveyor 7437

December 10, 2009

4888129

INDEXED ON MAP 6340 4D-/ REC'D 12-17-09 8MM OKV

Lee Surveying and Mapping Co., Inc.

Land Surveys . Topography . Subdivisions . Construction Layout

117 N. Madriver St. Bellefontaine OH 43311



Phone: (937) 593-7335 Fax: (937) 593-7444 surveys@lsminc.us

MOOTS 1.969 ACRES

Lying in Virginia Military Survey 12099, Monroe Township, Logan County, Ohio.

Being all of the Philip Moots two acre tract as deeded and described in Volume 43, Page 172 of the Logan County Records of Deeds and being more particularly described as follows:

Commencing on a MAG nail set on the south line of Virginia Military Survey 12099 on the center-line of Township Road 166.

THENCE, with the south line of Virginia Military Survey 12099, N 74°-44'-15"E, a distance of 938.24 feet to a 5/8 inch iron rod set at the TRUE POINT OF BEGINNING.

THENCE, with the east line of the Julie A. Walborn 9.5 acre tract (O.R. 859, Pg. 894), N 16°-15'-14"W, a distance of 349.92 feet to a 5/8 inch iron rod set, passing a 5/8 inch iron rod set at 30.00 feet.

THENCE, with the south line of the James E. Gantz and LaDonna F. Gantz, Trustees, 182.937 acre tract (O.R. 820, Pg. 627), N 76°-11'-06"E, a distance of 247.50 feet to a 5/8 inch iron rod found.

THENCE, with the west line of the George R. Kern, Jr., 1.536 acre tract (O.R. 251, Pg. 709), S 16°-17'-06"E, a distance of 343.67 feet to a point on the south line of Virginia Military Survey 12099, passing a 5/8 inch iron rod set at 313.67 feet and a railroad spike found (Station 49+83.75) on the center-line of pavement of Township Road 165 (60 feet wide) at 330.37 feet, said point referenced by a 5/8 inch iron rod found bearing S 25°-37'-17"E. a distance of 1.52 feet.

THENCE, with the south line of Virginia Military Survey 12099, S 74°-44'-15"W, a distance of 247.50 feet to the point of beginning.

Containing 1.969 acres, of which 0.170 acre is within the highway right-of-way.

The basis for bearings is the center-line of Township Road 165 between P.I. Station 44+15.04 and Station 49+83.75, being N 74°-48'-24"E, and all other bearings are from angles and distances measured in a field survey by Lee Surveying and Mapping Co., Inc. on December 8, 2009.

OF OF OWILLIAM OF REPORT OF THE PROPERTY OF TH

Description prepared by:

William K. Bruce Professional Surveyor 7437

December 10, 2009

4888129

INDEXED ON MAP 6340 4 D-2

