REC'D 5-16-06 SMAC

Lee Surveying and Mapping Co., Inc.

Land Surveys • Topography • Subdivisions • Construction Layout

117 N. Madriver St. Bellefontaine OH 43311



Phone: (937) 593-7335 Fax: (937) 593-7444

TROYER 112.826 ACRES

Lying in Virginia Military Survey 9931, McArthur Township, Logan County, Ohio.

Being all of the Leon H. Troyer and Ruth A. Troyer, as Trustee or the Successor Trustee of the Leon H. Troyer and Ruth A. Troyer Joint Revocable Trust dated June 22, 2005, 114.310 acre tract as deeded and described in Official Record 783, Page 983 of the Logan County Records of Deeds and being more particularly described as follows:

Beginning at a MAG nail found at the southeast corner of Virginia Military Survey 9931 on the center-line of Ohio Route 274.

THENCE, with the south line of Virginia Military Survey 9931 and the center-line of Ohio Route 274 (60 feet wide), S 82°-26'-00"W, a distance of 1586.59 feet to a MAG nail set.

THENCE, with the east lines of the Karl E. Harpest 125 acre tract (O.R. 565, Pg. 14) and the Steven Weaver 81.068 acre tract (O.R. 245, Pg. 888), N 7°-41'-07"W, a distance of 3072.60 feet to a 5/8 inch iron rod set, passing a 5/8 inch iron rod set at 30.00 feet.

THENCE, with the south line of the Helen Marie Cavin, et al 46.056 acre tract (O.R. 795, Pg. 001). N 82°-03'-53"E, a distance of 1607.14 feet to a 5/8 inch iron rod set on the east line of Virginia Military Survey 9931.

THENCE, with the east line of Virginia Military Survey 9931 and the west lines of the Leon H. Troyer and Ruth A. Troyer, as Trustee or the Successor Trustee of the Leon H. Troyer and Ruth A. Troyer Joint Revocable Trust dated June 22, 2005, 87.608 acre tract (O.R. 790, Pg. 106) and the Richard Dale Aiken 53.15 acre tract (Vol. 362, Pg. 35), S 7°-18'-13"E, a distance of 3082.96 feet to the point of beginning, passing a 5/8 inch iron rod set at 3052.96 feet.

Containing 112.826 acres, of which 1.093 acres are within the highway right-of-way.

EOF

LEE 6359

ONALS

ORIGINAL STAMP IN GREEN

ANNESSEE STATES

The basis for bearings is the center-line of Ohio Route 274, being S 82°-26'-00"W, and all other bearings are from angles and distances measured in a field survey by Lee Surveying and Mapping Co., Inc. on May 9, 2006.

Description prepared by:


Jeffrey I. Lee

Professional Surveyor 6359

May 9, 2006

4229046





INDEXED ON MAP

Lee Surveying and Mapping Co., Inc.

Land Surveys . Topography . Subdivisions . Construction Layout

117 N. Madriver St. Bellefontaine OH 43311



Phone: (937) 593-7335 Fax: (937) 593-7444

TROYER 46.977 ACRE

Lying in Virginia Military Survey 9931, McArthur Township, Logan County, Ohio.

Being out of the Leon H. Troyer and Ruth A. Troyer, as Trustee or the Successor Trustee of the Leon H. Troyer and Ruth A. Troyer Joint Revocable Trust dated June 22, 2005, 114.310 acre tract as deeded and described in Official Record 783, Page 983 of the Logan County Records of Deeds and being more particularly described as follows:

Commencing at a MAG nail found at the southeast corner of Virginia Military Survey 9931 on the center-line of Ohio Route 274.

THENCE, with the south line of Virginia Military Survey 9931 and the center-line of Ohio Route 274 (60 feet wide), S 82°-26'-00"W, a distance of 904.13 feet to a MAG nail set at the TRUE POINT OF BEGINNING.

THENCE, with the south line of Virginia Military Survey 9931 and the center-line of Ohio Route 274, S 82°-26'-00"W, a distance of 682.46 feet to a MAG nail found.

THENCE, with the east lines of the Mary E. Rostorfer 125 acre tract (O.R. 906, Pg. 786) and the Lloyd Gingerich etal 86.254 acre tract (O.R. 826, Pg. 141, Tract I), N 7°-41'-07"W, a distance of 3072.60 feet to a 5/8 inch iron rod found, passing a 5/8 inch iron rod found at 30.00 feet.

THENCE, with the south line of the Helen Marie Cavin, etal 46.056 acre tract (O.R. 795, Pg. 001), N 82°-03'-53"E, a distance of 648.59 feet to a 5/8 inch iron rod set.

THENCE, S 08°-18'-58"E, a distance of 3077.03 feet to the point of beginning, passing a 5/8 inch iron rod set at 3047.03 feet.

Containing 46.977 acres, of which 0.470 acre is within the highway right-of-way.

The basis for bearings is the center-line of Ohio Route 274, being S 82°-26′-00″W, and all other bearings are from angles and distances measured in a field survey by Lee Surveying and Mapping Co., Inc. on February 27, 2009.

BRUCE AND SOME SOME ORIGINAL STAMP IN GREEN

Description prepared by:

William K. Bruce Professional Surveyor 7437 February 27, 2009

11/1 / K. Brus o

4229029



2 WORKING DAYS

CALL TOLL FREE 800-362-2764

OHIO UTILITIES PROTECTION SERVICE.

BEFORE YOU DIG

BRUCE X BRUCE TASTONAL SURGINAL STAMP IN GREEN

WILLIAM K. BRUCE
PROFESSIONAL SURVEYOR 7437
FEBRUARY 27, 2009

FEBRUARY 27, 2009

COPYRIGHT 2009 BY:

LEE SURVEYING & MAPPING CO., INC.
117 North Madriver Street
BELLEFONTAINE, OHIO 43311
(937) 593-7335

KSS D0209

4229029 L-4229-2

INDEXED ON MAP



INNOVATIVE IDEAS **EXCEPTIONAL DESIGN** UNMATCHED CLIENT SERVICE

DUTTON 7.000 ACRES

Lying in Virginia Military Survey 12168, McArthur and Washington Townships, Logan County, Ohio (all records referenced herein refer to the Logan County Records of Deeds).

Being out of the James L. Dutton and Patricia A. Dutton original 74.55 acre tract as deeded and described in Official Record 1307, Page 35, Parcel III, and the James L. Dutton and Patricia A. Dutton 44.456 acre tract as deeded and described in Official Record 1308, Page 419, Parcel II, and being more particularly described as follows:


COMMENCING at a MAG nail found at the centerline intersection of State Route 274 (60 feet wide) and Township Road 95 and also being the common corner to said Virginia Military Survey 12168 and Virginia Military Surveys 9902, 10434 and 12052;

THENCE, South 83°-08'-55" West, with the centerline of said State Route 274 and the common line to said Virginia Military Surveys 12168 and 12052, a distance of 2039.19 feet to a MAG nail set at a common corner to the northwest corner of the Randall W. Benedict 3.674 acre tract as deeded and described in Official Record 1038, Page 565 and the northeast corner of said 44.456 acre tract and being the TRUE POINT OF **BEGINNING:**

THENCE, with common lines to said 44.456 acre and 3.674 acre tracts, the following two (2) courses:

- 1) South 04°-16'-49" West, passing a 5/8 inch iron rebar found (I.D. cap stamped "CLAPSADDLE RS6140") at a distance of 30.59 feet, a total distance of 333.63 feet to a 5/8 inch iron rebar found; and
- 2) South 08°-29'-33" East, a distance of 354.57 feet to an iron rebar set, said iron rebar set bearing North 08°29'33" West, a distance of 13.74 feet from a 5/8 inch iron rebar found (North 08°29'33" West, a distance of 6.26 from the southwest corner of said 3.674 acre tract) and said iron rebar set also being 7.9' north of the north bank of a creek;

THENCE, South 87°-24'-52" West, with a new division line through said 44.456 acre and 74.55 acre tracts, a distance of 451.63 feet to a 5/8 inch iron rebar set;



117 N Madriver St, Bellefontaine, OH 43311 OFFICE 937.593.7335 ONLINE WWW.DLZ.COM



INNOVATIVE IDEAS
EXCEPTIONAL DESIGN
UNMATCHED CLIENT SERVICE

THENCE, **North 06°-51'-05" West**, passing an iron rebar set at a distance of 618.19 feet, a total distance of **648.19 feet** to a MAG nail set on said centerline and common Virginia Military Survey line;

THENCE, **North 83°-08'-55" East**, with said centerline and common Virginia Military Survey line, a distance of **504.64 feet** to the **POINT OF BEGINNING**.

Containing **7.000** acres, more or less, of which 0.346 acre is within highway right-of-way, 0.320 acre is within McArthur Township, 6.680 acres within Washington Township, 2.210 acres out of said 74.55 acre tract and 4.790 acres out of said 44.456 acre tract.

Iron rebar set, where indicated, are 30 inches in length, 5/8 inch in diameter with a plastic I.D. cap stamped "DLZ OHIO INC.".

Property is subject to any and all previous easements and rights-of-way of record.

Bearings and distances, described herein, are derived from GPS observations based on Grid North, Ohio State Plane Coordinate System, North Zone, NAD83 (2011, Epoch 2010), with the centerline of State Route 274 having a bearing of North 83°-08'-55 East. Distances are expressed in U.S. Survey Feet. All other measurements are from angles and distances measured in a field survey by DLZ on July 14, 2020.

Description prepared by:

Daniel A. Neer

Professional Surveyor No. 8533

July 14, 2020

DANIEL A. NEER S-8533

INDEXED ON MAP

THIS SURVEY WAS PREPARED IN THE ABSENCE OF A COMPLETE AND ACCURATE TITLE SEARCH AND DOES NOT GUARANTEE TITLE.

NO EVIDENCE OF OCCUPATION ALONG BOUNDARY LINES UNLESS OTHERWISE SHOWN

OCCUPATION NOTE:

BEARINGS AND DISTANCES, SHOWN HEREON, ARE DERIVED FROM GPS OBSERVATIONS BASED ON GRID NORTH, OHIO STATE PLANE COORDINATE SYSTEM, NORTH ZONE, NAD83 (2011, EPOCH 2010), WITH THE CENTER-LINE OF STATE ROUTE 274, HAVING A BEARING OF N 83'08'55" E.

BASIS FOR BEARINGS:

7

Ţ,

10.0

V.M.S. 12168
WASHINGTON & MCARTHUR TOWNSHIPS
LOGAN COUNTY, OHIO

REV. NO.

DATE

7/14/20

7.000 ACRES

(OF WHICH 0.346 ACRE LIES
WITHIN THE HIGHWAY RIGHT-OF-WAY) 87°24'52" W 4.790 ACRES 7.210 JAMES L. DUTTON AND PATRICIA A. DUTTON O.R. 1308, PG. 419
44.456 ACRES
PARCEL II 451.63 (I.D. CAP STAMPED—"CLAPSADDLE RS6140") SURVEY WASHINGTON TOWNSHIP McARTHUR TOWNSHIP 6.680 ACRES 0.320 ACRE DANIEL A
NEER
S-8533
S-8533
REGISTERS
OR
NICHTON 78 S 04°16'49" W 2 08.53,33, E 324.57 333.63 DAN DRAWN BY: N 08*29*33" W 13.74' 6.26' RANDALL W. BENEDICT O.R. 1038, PG. 565 3.674 ACRES A) DANIEL A. NEER PROFESSIONAL SURVEYOR NO. 8533 JULY 14, 2020 LEGEND: 0 DESCRIPTION PG. = PAGE
V.M.S. = VIRGINIA MILITARY SURVEY
P.O.C. = POINT OF COMMENCEMENT
P.O.B. = POINT OF BEGINNING
T/B = TOP OF BANK C/L = CENTERLINE
R/W = RIGHT-OF-WAY
O.R. OFFICIAL RECORD 5/8 INCH \times 30 INCH IRON REBAR SET (I.D. CAP STAMPED "DLZ OHIO INC.") MAG NAIL SET MAG NAIL FOUND 5/8 INCH IRON REBAR FOUND

.61.848 W "20'12'80 N

James L. Dutton and Patricia A. Dutton O.R. 1307, PG. 35
ORIGINAL 74.55 ACRES PARCEL III

WASHINGTON TOWNSHIP McARTHUR TOWNSHIP DEED LOGAN COUNTY LOG-274-5.05 R/W PLAN LOGAN COUNTY ENGINEER'S MAP ROOM FILES - 1541, 9174, 9510 ૹ SURVEY REFERENCES:

REFERENCE DEEDS SHOWN HEREON

 $\frac{\dot{}}{\omega}$ 2020

<

<u>ē</u>,

<u>S</u>

SCALE: 1" = 100" DISTANCES SHOWN HEREON ARE IN U.S. SURVEY FEET

V.M.S. 12052 V.M.S. 12168

83°08'55" E

504.64

30.59'

P.O.B.

26 DAOR AIHRIMOT 1/21/28)

C/L

R∕¥

14.M.S. 9902

S 83'08'55"

R/W 2039.19

P.O.C.

TERCI. SWIN

(V.M.S. 10434

60,

MDE)

274